Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-606-5812

Section Quantity:

1

Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.875 inches **Body Diameter:** Between 0.632 inches and 0.642 inches Shaft Diameter: Between 0.151 inches and 0.161 inches Shaft Length: Between 0.469 inches and 0.531 inches Mounting Bushing Length: 0.375 inches **Body Length:** Between 0.359 inches and 0.406 inches **Overall Diameter:** 0.810 inches Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

100.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0