

View Online at <https://aerobasegroup.com/nsn/5905-00-607-0391>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

2.937 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Body Length:

2.875 inches

Overall Diameter:

2.000 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0940 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

2.25 inch-ounces

Maximum Running Torque:

1.75 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

20.0 percent, rated amperes c and better finish

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

360.0 1st section and 720.0 1st section and 1080.0 1st section and 1440.0 1st section and 1800.0 1st section and 2160.0 1st section and 2520.0 1st section and 2880.0 1st section and 3240.0 1st section

Rotary Actuator Travel In Angular Deg:

3780.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 2nd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 all sections

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

9 1st section

Tap Location Tolerance Per Section:

-3.0/+3.0 degrees angular rotation 1st section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

15 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0