Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-607-3253

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.3125 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.313 inches

Undercut Width:

0.0740 inches

Body Diameter:

1.437 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Body Length:

2.000 inches

Mounting Lip Diameter:

1.4370 inches

Mounting Lip Depth:

0.0940 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

77.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



Power Dissipation Rating Per Section In Watts: 5.0 free air single section **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -0.5 to 0.5 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops **Tap Location From Ccw Terminal Per Section In Ohms:** 3850.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig:

A002a0
