## NSN 5905-00-607-7310

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-607-7310

Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Terminal Type: Wire lead  Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001  Terminal Length: 1.250 inches  Body Diameter: 0.090 inches  Body Length: 0.431 inches
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.0001  Terminal Length: 1.250 inches  Body Diameter: 0.090 inches  Body Length: 0.431 inches
Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent: 0.0001  Terminal Length: 1.250 inches  Body Diameter: 0.090 inches  Body Length: 0.431 inches  Power Dissipation Rating In Watts:
Established  Reliability Failure Rate Level In Percent:  0.0001  Terminal Length:  1.250 inches  Body Diameter:  0.090 inches  Body Length:  0.431 inches
Reliability Failure Rate Level In Percent:  0.0001 Terminal Length: 1.250 inches  Body Diameter: 0.090 inches  Body Length: 0.431 inches
0.0001 Terminal Length: 1.250 inches Body Diameter: 0.090 inches Body Length: 0.431 inches
Terminal Length:  1.250 inches  Body Diameter:  0.090 inches  Body Length:  0.431 inches
1.250 inches  Body Diameter: 0.090 inches  Body Length: 0.431 inches
Body Diameter:  0.090 inches  Body Length:  0.431 inches
0.090 inches  Body Length: 0.431 inches
Body Length: 0.431 inches
0.431 inches
Power Dissipation Rating In Watts:
· · · · · · · · · · · · · · · · · · ·
2.250 free air
Terminal Width:
0.021 inches
Style Designator:
Axial terminal each end
Test Data Document:
94756-443-0955 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0