Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-608-3329

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
Between 0.175 inches and 0.225 inches
Body Diameter:
Between 0.250 inches and 0.260 inches
Body Length:
Between 0.160 inches and 0.180 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
230.0
Mounting Facility Quantity:
3
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.000 megohms single section
Rotary Actuator Travel In Angular Deg:
230.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0