NSN 5905-00-609-4719

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-609-4719 **Section Quantity: Body Style:** Cylindrical studs mounted First Flat Length: 0.375 inches Flat Height: 0.219 inches **Body Diameter:** 1.890 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 2.865 inches **Mounting Hole/stud Circle Diameter:** 1.666 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 40.0 **Mounting Facility Quantity:** 2 **Mounting Method:** Threaded stud **Electrical Resistance Per Section:** 2.250 kilohms all sections **Power Dissipation Rating Per Section In Watts:** 0.3 free air all sections **Resistance Tolerance Per Section In Percent:** -4.0/+4.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 75.0 all sections

Special Features:

Each section supplied with a matched fixed resistor

NSN 5905-00-609-4719

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0