

View Online at <https://aerobasegroup.com/nsn/5905-00-610-0549>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

Between 1.874 inches and 1.875 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.625 inches

Body Length:

1.576 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

1.90 inch-ounces

Maximum Running Torque:

1.20 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

8.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

50.0 all sections

Power Dissipation Rating Per Section In Watts:

2.8 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0