NSN 5905-00-610-4316

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-610-4316

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0
Electrical Resistance:
65.000 ohms
Resistance Tolerance In Percent:
-3.000/+3.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
7.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Height:
2.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0
-55.0/+275.0
-55.0/+275.0 Inclosure Method:
-55.0/+275.0 Inclosure Method: Encased
-55.0/+275.0 Inclosure Method: Encased Terminal Type:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches
Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches Power Dissipation Rating In Watts:
Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 12.500 free air

Axial terminals one end

NSN 5905-00-610-4316

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0