## NSN 5905-00-610-4382

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-610-4382

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.457 inches
Mounting Bushing Length:
0.313 inches
Body Length:
1.457 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

## NSN 5905-00-610-4382

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0