Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-614-5458

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

## **Terminal Length:**

0.175 inches

## Shaft Diameter:

0.100 inches

#### Shaft Length:

0.060 inches

### Body Length:

0.750 inches

### **Body Width:**

0.190 inches

## Body Height:

0.250 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7200.0

### Maximum Starting Torque:

5.00 inch-ounces

### Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.500 inches

### **Terminal Location:**

Lower adjacent side two rows

### **Mounting Method:**

Terminal

### Center To Center Distance Between Terminal Rows:

0.100 inches

## Features Provided:

Humidity proof

## **Electrical Resistance Per Section:**

20.000 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

7200.0



Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0