

View Online at <https://aerobasegroup.com/nsn/5905-00-614-8045>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5620 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.750 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.719 inches

Body Length:

1.442 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

1.10 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Function Conformity Per Section:

All sections absolute linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0