

View Online at <https://aerobasegroup.com/nsn/5905-00-615-1040>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.156 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.500 inches

**Body Length:**

1.266 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

292.0

**Maximum Starting Torque:**

18.00 inch-ounces

**Maximum Running Torque:**

18.00 inch-ounces

**Maximum Stop Torque:**

192.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Mechanical Backlash In Deg Angular Rotation:**

3.0

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

1.0 megohms all sections

**Rotary Actuator Travel In Angular Deg:**

312.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0 to 10.0 -55 degrees celsius all sections and +0.0 to 5.0 -25 degrees celsius all sections and +0.0 to 2.5 0 degrees celsius all sections and -3.5 to 3.5 85 degrees celsius all sections and +0.0 to 7.5 120 degrees celsius all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.5 free air 1st section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0