NSN 5905-00-615-1652

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-615-1652

| Body Style: |
|--|
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| First Flat Length: |
| 0.375 inches |
| Flat Height: |
| 0.216 inches |
| Body Diameter: |
| 1.094 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.750 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| 0.609 inches |
| Shaft Style: |
| Round, flatted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| |
| Standard bushing |
| Standard bushing Electrical Resistance Per Section: |
| • |
| Electrical Resistance Per Section: |

NSN 5905-00-615-1652

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|--|
| -10.0 to 10.0 single section |
| Standard Taper Curve Per Section: |

C single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0