## NSN 5905-00-615-3467

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-615-3467

Section Quantity:
2
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.156 inches
Shaft Length:
1.414 inches
Body Length:
2.250 inches
Body Width:
0.500 inches
Body Height:
0.875 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Longitudinal Actuator Travel:
0.645 inches
Longitudinal Actuator Effective Electrical Stroke Length:
0.645 inches
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
5.0 kilohms all sections
Function Conformity Tolerance Per Section:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 all sections

-0.50/+0.50 all sections

## NSN 5905-00-615-3467

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.25/+1.25 ohms all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 all sections
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 all sections
Special Features:
Mounting holes spaced 2.000 in. Center to center
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0