## NSN 5905-00-615-3822

**Section Quantity:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-615-3822

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.469 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.531 inches
Mounting Bushing Length:
0.188 inches
Body Length:
0.350 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
30.0 kilohms single section
<b>Function Conformity Tolerance Per Section:</b>
-0.05/+0.05 single section
Power Dissipation Rating Per Section In Watts:
6.9 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section

## NSN 5905-00-615-3822

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per S

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A002a0