NSN 5905-00-615-9384

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-615-9384 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.393 inches **Overall Height:** 0.375 inches **Overall Width:** 0.312 inches **Mounting Hole Diameter:** 0.090 inches **Shaft Diameter:** 0.156 inches **Shaft Length:** 0.047 inches **Body Length:** 1.393 inches **Body Width:** 0.312 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof

Electrical Resistance Per Section: 20.0 kilohms single section

NSN 5905-00-615-9384

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.8 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:** Demilitarization: No