NSN 5905-00-617-6811

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-617-6811 Section Quantity:

| Cylindrical |
|---|
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 0.358 inches |
| Terminal Length: |
| 0.188 inches |
| Body Diameter: |
| 0.500 inches |
| Shaft Diameter: |
| 0.140 inches |
| Shaft Length: |
| 0.100 inches |
| Body Length: |
| 0.170 inches |
| Overall Diameter: |
| 0.500 inches |
| Shaft Style: |
| Round, slotted |
| Shaft Bearing Type: |
| Bearing |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 300.0 |
| Maximum Running Torque: |
| 8.00 inch-ounces |
| Maximum Stop Torque: |
| 15.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.100 inches |
| Terminal Location: |
| Radially positioned over more than half the circumference |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 2.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |

NSN 5905-00-617-6811

Yes - demil/mli

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -4.0 to 4.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: