## NSN 5905-00-617-6811

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-617-6811 Section Quantity:

Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.358 inches
Terminal Length:
0.188 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.140 inches
Shaft Length:
0.100 inches
Body Length:
0.170 inches
Overall Diameter:
0.500 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Maximum Running Torque:
8.00 inch-ounces
Maximum Stop Torque:
15.00 inch-ounces
Center To Center Distance Between Terminals:
0.100 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0

## NSN 5905-00-617-6811

Yes - demil/mli

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -4.0 to 4.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: