## NSN 5905-00-617-7609

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-617-7609

| Townships Coefficient Of Resistance In Daw Dev Colsins  |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
| -30.0/+30.0   |
| Electrical Resistance:  |
| 100.000 kilohms   |
| Resistance Tolerance In Percent:  |
| -1.000/+1.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 125.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 145.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -65.0/+145.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 2.000 inches  |
| Body Diameter:  |
| 0.250 inches  |
| Body Length:  |
| 0.500 inches  |
| Power Dissipation Rating In Watts:  |
| 0.125 free air  |
| Cubic Measure (non-core):   |
| 0.025 cubic inches  |
| Unpackaged Unit Weight:   |
| 0.2 grams   |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 81349-mil-r-9444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Specification Data:   |
| 81349-mil-r-9444/1 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5905-00-617-7609

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0