## NSN 5905-00-617-8335

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-617-8335 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.864 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.130 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.516 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** 

Unthreaded hole **Electrical Resistance Per Section:** 2.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:** 

## NSN 5905-00-617-8335

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A002a0