

View Online at <https://aerobasegroup.com/nsn/5905-00-617-9517>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.8750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.781 inches

**Undercut Diameter:**

1.830 inches

**Undercut Width:**

0.0930 inches

**Body Diameter:**

2.000 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.562 inches

**Body Length:**

2.156 inches

**Overall Diameter:**

2.000 inches

**Mounting Lip Diameter:**

1.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3690.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

0.70 inch-ounces

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

1.600 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3690.0

**Function Conformity Tolerance Per Section:**

-0.03/+0.03 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Special Features:**

End terminals located 40 to 50 degrees from ends of element to insure 3600 degrees absolute linearity

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0