NSN 5905-00-617-9553

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-617-9553 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.425 inches **Undercut Diameter:** 1.3125 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.453 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.688 inches **Body Length:** 2.120 inches **Overall Diameter:** 1.812 inches **Mounting Lip Diameter:** 1.4380 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

1.40 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

NSN 5905-00-617-9553

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:				
0.00500 inches				
Shaft Runout:				
0.001 inches				
Lateral Runout:				
0.002 inches				
Pilot Diameter Runout:				
0.00200 inches				
Shaft Radial Play:				
0.002 inches				
Terminal Location:				
Radially positioned over less than half the circumference				
Mounting Method:				
Clamp ring				
Electrical Resistance Per Section:				
10.000 kilohms 1st section				
Rotary Actuator Travel In Angular Deg:				
360.0				
Function Conformity Tolerance Per Section:				
-0.25 to 0.25 3rd section				
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:				
50.0 all sections				
Power Dissipation Rating Per Section In Watts:				
2.0 free air all sections				
Function Conformity Per Section:				
All sections absolute linearity				
Resistance Tolerance Per Section In Percent:				
-5.0 to 5.0 all sections				
Actuator Travel Control Feature:				
Continuous motion				
Function Characteristic Per Section:				
All sections linear				
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:				
-20.0 to 20.0 all sections				
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:				
40.0 all sections				
Unpackaged Unit Weight:				
3.84 ounces				
Precious Material And Location:				
Terminals gold				
Precious Material:				
Gold				
Terminal Type And Quantity:				
9 turret				

NSN 5905-00-617-9553

Precision Wire Wound Variable Resistor - Page 3 of 3



She	Ιf	I it	i۵.
Olic	•••		С.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0