

View Online at <https://aerobasegroup.com/nsn/5905-00-617-9554>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.3110 inches and 1.3125 inches

Pilot Length:

0.0620 inches

Overall Length:

2.383 inches

Undercut Diameter:

1.453 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.438 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.657 inches and 0.719 inches

Body Length:

1.539 inches

Overall Diameter:

1.704 inches

Mounting Lip Diameter:

1.4380 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

1.60 inch-ounces

Maximum Running Torque:

1.10 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.000 kilohms all sections

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

177.0 all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation all sections

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0