NSN 5905-00-617-9765

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-617-9765

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.627 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.688 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.563 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.20 inch-ounces
Maximum Running Torque:
0.80 inch-ounces
0.80 inch-ounces Terminal Location:
Terminal Location:
Terminal Location: Radially positioned over less than half the circumference
Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.05/+0.05 single section
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.05/+0.05 single section Power Dissipation Rating Per Section In Watts:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.05/+0.05 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Flange Electrical Resistance Per Section: 5.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.05/+0.05 single section Power Dissipation Rating Per Section In Watts: 4.0 free air single section Function Conformity Per Section:

NSN 5905-00-617-9765

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: