

View Online at <https://aerobasegroup.com/nsn/5905-00-617-9769>

Section Quantity:

4

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Length:

0.0620 inches

Overall Length:

3.413 inches

Terminal Length:

0.254 inches

Undercut Diameter:

1.312 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.453 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.657 inches and 0.719 inches

Body Length:

2.660 inches

Overall Diameter:

1.707 inches

Mounting Lip Diameter:

1.4380 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

2.80 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Shaft End Play:

0.00100 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

50.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

345.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0