Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-619-3380

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.250 inches

**Body Length:** 

0.375 inches

**Body Width:** 

0.281 inches

**Body Height:** 

0.290 inches

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

360.0

#### **Center To Center Distance Between Terminals:**

0.200 inches

### **Terminal Location:**

Lower adjacent side two rows

#### Mounting Method:

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

337.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

360.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Continuous motion



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0