## NSN 5905-00-620-9688

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-620-9688 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Body Diameter:** 0.500 inches **Body Length:** 0.325 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 7.50 inch-ounces **Maximum Running Torque:** 7.50 inch-ounces **Maximum Stop Torque:** 30.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Cubic Measure:** 0.063 cubic inches **Electrical Resistance Per Section:** 10.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

## NSN 5905-00-620-9688

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.000 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No