NSN 5905-00-620-9726

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-620-9726

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.240 inches
Shaft Diameter:
0.070 inches
Shaft Length:
0.040 inches
Body Length:
0.500 inches
Body Width:
0.100 inches
Body Height:
0.150 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Center To Center Distance Between Terminals:
0.400 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

NSN 5905-00-620-9726

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	Tempurature	Coefficient Of	Resistance	Per Section	n In Ppm	Per Deg	Celsius:
--	-------------	----------------	------------	-------------	----------	---------	----------

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.6 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0