

View Online at <https://aerobasegroup.com/nsn/5905-00-622-2157>

**Section Quantity:**

3

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7497 inches

**Pilot Length:**

0.0650 inches

**Undercut Diameter:**

0.875 inches

**Undercut Width:**

0.0650 inches

**Body Diameter:**

0.883 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.470 inches

**Body Length:**

1.830 inches

**Mounting Lip Diameter:**

1.8300 inches

**Mounting Lip Depth:**

0.0650 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

350.0

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.555 percent, rated amperes c and better industrial clears

**Rotary Actuator Travel In Angular Deg:**

340.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 3rd section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-4.0/+4.0 1st section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0