## NSN 5905-00-622-4071

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-622-4071 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.547 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.578 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.969 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.431 inches **Screw Thread Diameter:** Radially positioned over less than half the circumference

0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location: Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 5.000 kilohms single section

## NSN 5905-00-622-4071

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
330.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: