Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-623-4750

Section Quantity: 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.202 inches Shaft Diameter: Between 0.055 inches and 0.060 inches Shaft Length: 0.030 inches **Body Length:** Between 0.522 inches and 0.538 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.482 inches and 0.508 inches Shaft Style: Round, slotted Shaft Bearing Type: Bearing Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 15120.0 Maximum Starting Torque: 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Terminal Location:** Rear end **Mounting Method:** Terminal **Cubic Measure:** 0.047 cubic inches **Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 15120.0



Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0