Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-624-4996

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

3.187 inches

#### First Flat Length:

Between 0.344 inches and 0.594 inches

Flat Height:

Between 0.211 inches and 0.221 inches

#### **Body Diameter:**

1.880 inches

#### Shaft Diameter:

Between 0.248 inches and 0.251 inches

#### Shaft Length:

Between 0.828 inches and 0.922 inches

# Mounting Bushing Length:

0.375 inches

# Body Length:

1.750 inches

#### **Overall Diameter:**

1.880 inches

#### Shaft Style:

Round, flatted

# Contact Arm Electrical Off Position:

Fully ccw

# Actuator Type:

Single shaft

# Nonturn Device Location:

At 12 oclock

# Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

# Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# NSN 5905-00-624-4996

N/a

No Fiig:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



# **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 25.000 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 280.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 12.5 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab w/screw **Specification Data:** 81349-mil-r-22/4 government specification Shelf Life: Unit Of Measure: **Demilitarization:** A002a0