NSN 5905-00-624-7434

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-624-7434 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 3.906 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 1.031 inches **Mounting Stud Length:** 0.312 inches **Body Length:** 2.875 inches **Overall Diameter:** 1.969 inches **Mounting Hole/stud Circle Diameter:** 1.125 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.001 inches

Shaft Radial Play: 0.005 inches

NSN 5905-00-624-7434

Precision Wire Wound Variable Resistor - Page 2 of 3



Fragility Factor: Moderately delicate **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 40.0 **Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded stud **Electrical Resistance Per Section:** 100.000 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.5 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Precious Material And Location:** Terminal surface silver **Precious Material And Weight:** 0.480 silver grains, troy **Precious Material:** Silver

12 tab, solder lug

Terminal Type And Quantity:

NSN 5905-00-624-7434

Precision Wire Wound Variable Resistor - Page 3 of 3



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0