NSN 5905-00-626-2586

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-626-2586 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.312 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.000 ohms single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

N/a

Shelf Life:

NSN 5905-00-626-2586

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0