Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-629-0065

Section	Quantity:	

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

### **Terminal Length:**

0.180 inches

**Body Length:** 

0.187 inches

**Body Width:** 

#### 0.375 inches

Body Height:

0.375 inches

#### Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

262.0

## Maximum Starting Torque:

5.00 inch-ounces

## Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### Cubic Measure:

0.026 cubic inches

#### **Electrical Resistance Per Section:**

1.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

360.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0