NSN 5905-00-629-0067

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-629-0067

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.180 inches
Body Length:
0.187 inches
Body Width:
0.375 inches
Body Height:
0.375 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
262.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Mounting Method: Terminal
Terminal
Terminal Cubic Measure:
Terminal Cubic Measure: 0.026 cubic inches
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section:
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section Rotary Actuator Travel In Angular Deg:
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Center To Center Distance Between Center Terminal And Outside Terminal:
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches
Terminal Cubic Measure: 0.026 cubic inches Electrical Resistance Per Section: 10.000 kilohms single section Rotary Actuator Travel In Angular Deg: 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-629-0067

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No