NSN 5905-00-630-4482

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-630-4482 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.350 inches **Mounting Bushing Length:** 0.300 inches **Body Length:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 150.000 ohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 all sections **Power Dissipation Rating Per Section In Watts:** 5.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Standard Taper Curve Per Section:

A all sections

40.0 all sections

NSN 5905-00-630-4482

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal | Type | And | Quantity: |
|----------|------|-----|-----------|
| | | | |

12 tab, solder lug

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0