NSN 5905-00-630-4603

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-630-4603 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.500 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 21.0 **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 35.000 ohms single section **Power Dissipation Rating Per Section In Watts:** 26.0 free air single section

-10.0 to 10.0 single section

Switch Current Type And Rating In Amps:

Resistance Tolerance Per Section In Percent:

1.500 ac/dc

NSN 5905-00-630-4603

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
S single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0