Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-630-5147

### Section Quantity:

2

# Body Style:

Cylindrical hole/slot mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

2.375 inches

#### **Body Diameter:**

1.906 inches

#### Mounting Hole Diameter:

0.177 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

#### 0.750 inches

Body Length:

#### 1.375 inches

Mounting Hole/stud Circle Diameter:

1.656 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### **Mounting Facility Quantity:**

4

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

200.000 ohms all sections

#### **Rotary Actuator Travel In Angular Deg:**

300.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

# Power Dissipation Rating Per Section In Watts:

6.0 free air all sections

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

#### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

### Terminal Type And Quantity:

3 connector, receptacle

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0