

View Online at <https://aerobasegroup.com/nsn/5905-00-632-9390>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.375 inches

Flat Height:

0.218 inches

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.562 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

315.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

315.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0