NSN 5905-00-636-5181

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-636-5181 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.500 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-636-5181

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0