NSN 5905-00-636-6623

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-636-6623

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.820 inches
Shaft Diameter:
0.250 inches
Shaft Length: 0.560 inches
Mounting Bushing Length:
0.375 inches
Body Length: 1.969 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method: Threaded hole
Features Provided:
Nonmetallic shaft Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0

-0.025/+0.025 single section

Function Conformity Tolerance Per Section:

NSN 5905-00-636-6623

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Tapped holes equally spaced on 1.250 in. Dia
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0