NSN 5905-00-636-6676

Fiig: A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-636-6676

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -260.0/+260.0 |
| Electrical Resistance: |
| 1.000 kilohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Ferrule |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.438 inches and 0.562 inches |
| Body Diameter: |
| Between 0.781 inches and 0.844 inches |
| Body Length: |
| Between 3.375 inches and 3.500 inches |
| Power Dissipation Rating In Watts: |
| 58.000 free air |
| Cubic Measure (non-core): |
| 1.957 cubic inches |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-26/1 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |