## NSN 5905-00-636-6741

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-636-6741

Tompurature Coefficient Of Registeres In Dam Box Dog Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -260.0 to 260.0
Electrical Resistance: 1.100 kilohms
Resistance Tolerance In Percent:
-5.000 to 5.000
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 350.0
Inclosure Method:
Encapsulated Torminal Types
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established  Terminal Longth:
Terminal Length:
0.453 inches
Body Diameter:
0.594 inches
Body Length:  Between 1.538 inches and 1.562 inches
Power Dissipation Rating In Watts:
14.000 free air  Err Default:
Between 0.172 inches and 0.328 inches
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-prf-26/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-26/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.

A001a0

Fiig:

## NSN 5905-00-636-6741

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-26 spec.