

View Online at <https://aerobasegroup.com/nsn/5905-00-638-6776>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 1.300 inches and 1.320 inches

**Shaft Diameter:**

0.188 inches

**Shaft Length:**

0.765 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

Between 0.615 inches and 0.635 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

350.0

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

140.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Fixed Tap Quantity Per Section:**

3 single section

**Tap Location Tolerance Per Section:**

-3.0 to 3.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

90.0 single section and 90.0 single section and 5000.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

80.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0