

View Online at <https://aerobasegroup.com/nsn/5905-00-642-0793>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.922 inches

Shaft Diameter:

0.265 inches

Shaft Length:

1.250 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.875 inches

Undercut Diameter:

0.187 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Undercut Length:

0.875 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.0 kilohms 2nd section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 all sections

Power Dissipation Rating Per Section In Watts:

0.25 heat sink all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0