

View Online at <https://aerobasegroup.com/nsn/5905-00-642-0799>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.344 inches

**Flat Height:**

0.188 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.625 inches

**Shaft Style:**

Round, parallel flatted

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

25.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

333.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

500.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

333.0

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Stops

**Switch Current Type And Rating In Amps:**

2.500 dc

**Standard Taper Curve Per Section:**

C single section

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0