NSN 5905-00-642-2731

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-642-2731 **Section Quantity:** 2 First Flat Length: 0.469 inches Flat Height: 0.218 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.031 inches **Mounting Bushing Length:** 0.562 inches **Overall Diameter:** 1.531 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms 2nd section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:**

Terminal Type And
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
--

NSN 5905-00-642-2731

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0