## NSN 5905-00-642-4805

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-642-4805

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.375 inches
Flat Height:
0.219 inches
Body Diameter:
4.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
2.000 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Distance Between Mounting Hole Centers:
1.750 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
readially positioned over less than that the circumstence
Mounting Method:
Mounting Method: Standard bushing Electrical Resistance Per Section:
Mounting Method: Standard bushing Electrical Resistance Per Section: 32.000 ohms single section
Mounting Method: Standard bushing Electrical Resistance Per Section:

-10.0 to 10.0 single section

## NSN 5905-00-642-4805

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0