## NSN 5905-00-642-4994

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-642-4994
Section Quantity:
2
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Overall Diameter:
1.062 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.000 megohms 2nd section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 2nd section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5905-00-642-4994

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0